

VIAVI

OLP-34/35/38

SmartPocket™ Optical Power Meters

VIAVI Solutions® OLP-3x optical power meters quickly, easily, and conveniently measure power levels and loss in fiber networks.

Pocket-Sized Power Meters for All Kinds of Applications

Easy-to-use for technicians at any skill level, SmartPocket optical power meters complement VIAVI optical light sources for insertion loss and continuity testing in both multimode and single-mode networks. They offer a dedicated and cost-optimized solution for testing and troubleshooting fiber in the field with:

- Intuitive, one-button operation
- Automatic wavelength recognition
- A large, sharp display that simultaneously shows relevant results and settings

The small and rugged OLP-3x also includes unprecedented data storage capacity and downloads results to a PC with a micro USB port.

- The OLP-34 is optimized for LAN/WAN access and enterprise networks and multimode or single-mode applications
- The OLP-35 is optimized for standard telecommunication network applications
- The OLP-38 is a higher-power (+26 dBm) version for CATV (with analog RF transmission) or amplified DWDM systems applications



Benefits

- Cost-effective, rugged high-performance solution
- 3-year recalibration period
- 1 nm incremental universal wavelength settings
- Universal optical interface supports all 2.5 mm with an option to support 1.25 mm connectors
- Auto wavelength detection and TwinTest mode
- Internal data storage and PC download capability
- Quick start operation eliminates warm-up

Applications

- Measuring optical power levels and link insertion loss
- Enterprise LAN networks with 850/1300 nm multimode wavelengths capability
- Test access and metro (LAN/WAN) networks in multimode and single-mode
- Standard and high-power level tests for use in telecom, CATV, and military applications

A Small Tool with Big Capabilities

Large, sharp screen displays:

- Battery level status
- Power mode (PERM, ECON)
- Measurement results in dBm/W/dB
- Wavelength setting
- Auto wavelength detection
- Tone detection

Straightforward 4-button operation



Rugged, shock resistant, and splash-proof design

3-way power

- AA dry
- AA rechargeable
- AC operation



SmartPocket OMK-3x optical test kits include an OLS-3x optical light source, an OLP-3x optical power meter, and accessories

Test and Report Field Measurements

VIavi Smart Reporter reporting software lets users quickly and efficiently download test results data from the power meter's memory with just a few clicks. After it's downloaded, the software reporting functions let users generate and customize professional certification reports.



Report date: Tuesday, 7 June 2016

OLP-34/35/38 Report - my Report 01

Technician Information

Company Name: Viavi
 Technician Name: Mustermann
 Address: Arbochtalstr 5
 Postal Code: 72800
 City: Erlangen
 Country: Germany



Measurement results

Fiber ID	λ [nm]	Power [dBm]	Power [µWatt]	Power [dB]	Reference [dBm]	Mod.Freq. [Hz]
5	1310			-4.57	-3.25	
7	1490			-4.19	-6.07	
8	1310			-6.83	-3.25	270
9	1310			-4.10	-3.25	1000
10	1550			-4.13	-3.45	1000
11	1550	-3.98				
12	1550	-3.98				
13	1310	-4.33				
14	1310		369.30			
15	1550		400.90			

Technical Specifications

	O LP-34	O LP-35	O LP-38
Detector type	InGaAs	InGaAs	Filtered InGaAs
Optical interface/connectors	Universal 2.5 mm/1.25 mm ¹	Universal 2.5 mm/1.25 mm ¹	Universal 2.5 mm/1.25 mm ¹
Wavelength range	780 to 1600 nm	780 to 1650 nm	780 to 1650 nm
Wavelength settings	780 to 1600 nm, step size 1 nm	780 to 1650 nm, step size 1 nm	780 to 1650 nm, step size 1 nm
Programmable wavelengths	5 presets (customized)	5 presets (customized)	5 presets (customized)
Calibrated wavelengths	850, 980, 1310, 1490, 1550 nm	850, 980, 1310, 1490, 1550, 1625 nm	850, 980, 1310, 1490, 1550, 1625 nm
Power range	-60 to +5 dBm	-65 to +10 dBm	-50 to +26 dBm
Display range	-60 to +10 dBm	-65 to +13 dBm	-50 to +26 dBm
Max. input power	+13 dBm	+16 dBm	+27 dBm
Measurement units	dB/dBm/W	dB/dBm/W	dB/dBm/W
Intrinsic uncertainty ²	±0.2 dB (±5%)	±0.2 dB (±5%)	±0.2 dB (±5%)
Linearity ³	±0.06 dB (-50 to +5 dBm)	±0.06 dB (-50 to +5 dBm)	±0.06 dB (-32 to +20 dBm)
Tone detection	270 Hz, 1 kHz, 2 kHz	270 Hz, 1 kHz, 2 kHz	270 Hz, 1 kHz, 2 kHz
Auto λ mode ⁴	Yes	Yes	Yes
Multi λ mode ⁴	TwinTest/serial TripleTest	TwinTest/serial TripleTest	TwinTest/serial TripleTest

Notes:

- Optional 1.25 mm UPP accessory adapter is available.
- Under these reference conditions: -20 dBm (CW), 1310 nm ±1 nm, 23°C ±3K, 5 to 75% relative humidity 9 to 50 μ m test fiber with ceramic DIN connector.
- 5 to +45°C.
- With VIAVI light sources.

General (typical at 25°C)

Storage and Interface

Data storage	100 results
Data download capability	Micro USB interface for PC transfer

Power Supply

Dry batteries	2x Mignon (AA) 1.5 V
Rechargeable batteries	2x Mignon (AA) NiMH 1.2 V
AC operation	Via micro USB and SNT-505
Battery life	≥200 hr Automatic power off after 20 minutes

Environmental Conditions

EMI/ESD	CE compliant
Recommended calibration interval	3 years
Operating temperature	-10 to +55°C (+14 to +131°F)
Storage temperature	-40 to +70°C (-40 to +158°F)
Dimensions (H x W x D)	30 x 80 x 150 mm (1.2 x 3.1 x 5.9 in)
Weight	200 g (0.45 lb)

Ordering Information

Description	Part Number
OLP-34 optical power meter InGaAs, +5 dBm with data storage and USB download capability	2302/11
OLP-35 optical power meter InGaAs, +10 dBm with data storage and USB download capability	2302/12
OLP-38 optical power meter Filtered InGaAs, +26 dBm with data storage and USB download capability	2302/13

Each optical power meter includes a 2.5 mm UPP adapter, AA alkaline batteries, a quick start guide, neck strap, a belt bag, and a USB connection cable.

Description	Part Number
Optional Accessories	
Fiber cleaning consumables kit	FCR-CLN-01
NiMH rechargeable batteries, Mignon AA, 1.2 V (2 batteries required)	2237/90.02
SNT-505; universal AC power adapter, micro USB connector	2302/90.01
UPP adapter for LC, MU (1.25 mm)	2256/90.03
USB connection cable	K 807
Smart Reporter (free download from http://www.updatemyunit.net/)	

VIAVI Care Support Plans

Increase your productivity for up to 5 years with optional VIAVI Care Support Plans:

- Maximize your time with on-demand training, priority technical application support and rapid service.
- Maintain your equipment for peak performance at a low, predictable cost.

For more Information: go to viavisolutions.com/viavicareplan

Features

*5-year plans only

Plan	Objective	Technical Assistance	Factory Repair	Priority Service	Self-paced Training	5 Year Battery and Bag Coverage	Factory Calibration
 BronzeCare	Technician Efficiency	Premium	✓	✓	✓		
 SilverCare	Maintenance & Measurement Accuracy	Premium	✓	✓	✓	✓*	✓



Contact Us **+1 844 GO VIAVI**
(+1 844 468 4284)

To reach the VIAVI office nearest you,
visit viavisolutions.com/contact

© 2020 VIAVI Solutions Inc.
Product specifications and descriptions in this document are subject to change without notice.
OLP-34-35-38-ds-fop-tm-ae
30162955 906 0120