

## 2F Indoor Termination Box

2 Fiber Splice Capacity, 2 Patch Ports(RJ45+(SC or LC))

ITB-11080-1SC-1RJ45-2S-3P is a very compact termination box for maximum 2 FO connectors and 1 RJ-45 or RJ-11 copper connector.

The box provides mechanical protection for the fiber and permits appropriate access while maintaining the highest standards of fiber management. The box is typically used at the customer premises in the termination part of the access network

### Features

- Can be used flush mounted or surface mounted
- Compatible with almost any standard electricity box
- Compatible with 250 micron and 900 micron fiber types
- Removable fiber organizer system for easy installation
- Can be used with field installable connectors or fusion splices
- Guaranteed minimum bending radius of 20mm
- One SC or duplex LC connector footprint
- Splice-through allows moving access points within the premise
- Provide a clean upgrade path from copper to fiber
- Environmental friendly materials, low smoke zero halogen
- Cable entry points : back, bottom, side

### Specifications

Model No.	ITB-11080-1SC-1RJ45-2S-3P 2 Splice Capacity, 1 SC + 1 RJ45 Adapters, 3 Drop Ports
Spliced Fiber Capacity	2 splices
Size   H x L x W	110mm x 80mm x 24mm
Cable Ports	2 patch ports, 3 round ports (10mm)

