

## 48F Indoor Termination Box

144 Fiber Splice Capacity, 48 Patch Ports

ITB-398327-54SC-144S-48P is a compact fiber terminal for use at the final fiber termination point in the customer premises.

The ITB-398327-54SC-144S-48P provides mechanical protection and managed fiber control in an attractive format suitable for use inside customer premises.

A variety of possible fiber termination techniques are accommodated.

### Features

- The oval port is for 1 loop for 2 cables with max Ø 20 mm.
- The reserved port is for cables with max Ø 18 mm
- Bending radius > 30mm
- Designed for Wall and Pole mount applications
- Safety lock
- Rugged and durable and UV resistant
- Design for small and medium volumes of fiber optic cables
- Reusable
- ROHS compliance
- Dimensions 398 mm x 327 mm x 118 mm (L x W x H)

### Specifications

Model No.	ITB-398327-54SC-144S-48P
Capacity	144 splices / 54 SC-SX
Splitter Capacity	PLC 6x 1/8 or 3x 1/16 or 1x 1/32
Cable Ports	2 cable ports - max Ø 20mm 1 reserved cable port - max Ø 18mm
Drop Cable	12 ports - max Ø 14mm that holds 48 drop cables - max Ø 3mm
Size   H x L x W	398mm x 327mm x 118mm
Application	Wall & Pole mounted

