90° Keystone Jacks | UnShielded | Tool Free

Product Code	Product Description
RJ45F-RJ45F-C06-US-90	Category 6 Jack to Jack Keystone UnShielded
RJ45F-RJ45F-C6A-US-90	Category 6A Jack to Jack Keystone UnShielded



Features

Compatible both T568A and T568B wiring schemes.DELTA and ETL verified CAT6 and CAT6A component-rated performanceUL safety listedTool free type, easy installation.Copper wire gauge: 23AWG to 26AWGCable outer diameter: 5.0 to 8.0mmEasily snap in and out of patch panel, and surface boxes or other application.UL Certified & RoHS Compliant.PoE plus IEC60512-99-001 verified by DELTAL x W x H: 37.8 x 16.8 x 22.7mm

Easy Crimp Tool - 2

Suitable for RJ45F-RJ45F-C06-US-90 Suitable for RJ45F-RJ45F-C6A-US-90 Light weight by plastic material design Economic solution for keystone jack and field termination plug installation



90° Keystone Jacks | Shielded | Tool Free

Product Code	Product Description
RJ45F-RJ45F-C06-FS-90	Category 6 Jack to Jack Keystone Shielded
RJ45F-RJ45F-C6A-FS-90	Category 6A Jack to Jack Keystone Shielded
<image/>	<image/>
Features	
Compatible both T568A and T568B wiring sche	emes.
Full shielded by zinc alloy housing	

DELTA and ETL verified CAT6 and CAT6A component-rated performance

UL safety listed

Tool free type, easy installation.

Copper wire gauge: 23AWG to 26AWG

Cable outer diameter: 5.0 to 8.0mm

Easily snap in and out of patch panel, and surface boxes or other application.

UL Certified & RoHS Compliant.

PoE plus IEC60512-99-001 verified by DELTA

L x W x H: 37.8 x 16.8 x 22.7mm

Easy Crimp Tool - 2

Suitable for RJ45F-RJ45F-C06-FS-90 Suitable for RJ45F-RJ45F-C6A-FS-90 Light weight by plastic material design Economic solution for keystone jack and field termination plug installation



180° Keystone Jacks | UnShielded | Tool Free

Product Code	Product Description
RJ45F-RJ45F-C06-US-180	Category 6 Jack to Jack Keystone UnShielded
RJ45F-RJ45F-C6A-US-180	Category 6A Jack to Jack Keystone UnShielded



Features

Compatible both T568A and T568B wiring schemes.

DELTA and ETL verified CAT6 and CAT6A component-rated performance

UL safety listed

Tool free type, easy installation.

Copper wire gauge: 23AWG to 26AWG

Cable outer diameter. 5.0 to 8.0mm

Easily snap in and out of patch panel, and surface boxes or other application.

UL Certified & RoHS Compliant.

PoE plus IEC60512-99-001 verified by DELTA

L x W x H: 37.8 x 16.8 x 22.7mm

Easy Crimp Tool - 1

Suitable for RJ45F-RJ45F-C06-US-180 Suitable for RJ45F-RJ45F-C6A-US-180 Light weight by plastic material design Economic solution for keystone jack and field termination plug installation



180° Keystone Jacks | Shielded | Tool Free

Product Code	Product Description
RJ45F-RJ45F-C06-FS-180	Category 6 Jack to Jack Keystone Shielded
RJ45F-RJ45F-C6A-FS-180	Category 6A Jack to Jack Keystone Shielded
Features	

Compatible both T568A and T568B wiring schemes. Full shielded by zinc alloy housing DELTA and ETL verified CAT6 and CAT6A component-rated performance UL safety listed Tool free type, easy installation. Copper wire gauge: 23AWG to 26AWG Cable outer diameter. 5.0 to 8.0mm Easily snap in and out of patch panel, and surface boxes or other application. UL Certified & RoHS Compliant. PoE plus IEC60512-99-001 verified by DELTA L x W x H: 37.8 x 16.8 x 22.7mm

Easy Crimp Tool - 1

Suitable for RJ45F-RJ45F-C06-FS-180 Suitable for RJ45F-RJ45F-C6A-FS-180 Light weight by plastic material design Economic solution for keystone jack and field termination plug installation

